

BT14B-BS

BS CODE: **300629**

VOLTAGE **12V**

CCA **210A**

CAPACITY 20HR **12.6Ah**

CAPACITY 10HR **12.0Ah**



DIMENSIONS

LENGTH	150 ±2mm	5.91 ±0.08inch
WIDTH	70 ±2mm	2.76 ±0.08inch
TOTAL HEIGHT	145 ±2mm	5.71 ±0.08inch
WEIGHT	3.07 kg ±5%	6.77 lbs ±5%

Technical drawings showing front, side, and top views of the battery. Dimensions include length (150 ±2mm), width (70 ±2mm), and total height (145 ±2mm). A detail view of the terminal area shows a 'DO NOT OPEN' warning and dimensions for the terminal spacing (121.6 ±0.5mm) and terminal width (70 ±2mm).

TERMINAL (mm)

POLARITY		
-----------------	--	--

Terminal diagrams showing front, side, and top views. Dimensions include terminal width (11.5mm), terminal height (7.5mm), and terminal diameter (φ5.2mm). The front view shows a terminal height of 12mm and a distance of 15.8mm from the bottom edge to the center of the terminal.

MF FEATURES

- TO BE ACTIVATED**
AGM (Absorbent Glass Mat) technology.
- ACID PACK INCLUDED**
For initial filling.
- NO MAINTENANCE***
VRLA (Valve Regulated Lead Acid) design.
- TIGHTLY SEALED AFTER FILLING**
Electrolyte is held in a glass fiber mat.
- SUPERIOR POWER & EXTENDED CYCLE LIFE**
- LONG SHELF LIFE**
No need to be recharged while stocked (if not activated).

*once activated

MOUNTING ANGLE

Mounting angle diagrams showing the battery can be tilted at 25°, 0°, or 25° for the first configuration, and 20°, 0°, or 10° for the second configuration.

UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	-