

## BTX14-BS

BS CODE: 300604

VOLTAGE **12V**

CCA **200A**


CAPACITY 20HR **12.6Ah**

CAPACITY 10HR **12.0Ah**



### DIMENSIONS

<b>LENGTH</b>	150 ±2mm	5.91 ±0.08inch
<b>WIDTH</b>	87 ±2mm	3.43 ±0.08inch
<b>TOTAL HEIGHT</b>	145 ±2mm	5.71 ±0.08inch
<b>WEIGHT</b>	3.2 kg ±5%	7.05 lbs ±5%




### MF FEATURES


- TO BE ACTIVATED**  
AGM (Absorbent Glass Mat) technology.
- ACID PACK INCLUDED**  
For initial filling.
- NO MAINTENANCE\***  
VRLA (Valve Regulated Lead Acid) design.
- TIGHTLY SEALED AFTER FILLING**  
Electrolyte is held in a glass fiber mat.
- SUPERIOR POWER & EXTENDED CYCLE LIFE**
- LONG SHELF LIFE**  
No need to be recharged while stocked (if not activated).

\*once activated

### MOUNTING ANGLE



### TERMINAL (mm)



### UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	-