

BB12A-A /12N12A-4A-1

BS CODE: 310561

VOLTAGE **12V**

CCA **155A**

CAPACITY 20HR **12.6Ah**

CAPACITY 10HR **12.0Ah**



DIMENSIONS

LENGTH	134 ±2mm	5.28 ±0.08inch
WIDTH	81 ±2mm	3.19 ±0.08inch
TOTAL HEIGHT	160 ±2mm	6.3 ±0.08inch
WEIGHT	2.88 kg ±5%	6.35 lbs ±5%

Technical drawings showing front, side, and top views of the battery with dimensions: 160 ±2 (height), 81 ±2 (width), 107 ±0.5 (terminal length), 134 ±2 (length), 144 ±2 (length), and 27 ±0.5 (terminal offset).

TERMINAL (mm)

POLARITY	⊕ / ⊖	
FRONT	SIDE	TOP

DRY FEATURES

- TO BE ACTIVATED**
DRY-charged technology.
- ACID PACK INCLUDED**
For initial filling.
- PERIODIC MAINTENANCE**
Refilled with water if necessary.
- HANDLE WITH CARE TO PREVENT ACID SPILLAGE**
- LONG SHELF LIFE**
No need to be recharged while stocked (if not activated).
- INTERNAL GAS EMISSION THROUGH VENTING HOLE**
- WIDE VARIETY OF 6V & 12V MODELS**

MOUNTING ANGLE

Diagram illustrating the mounting angle of the battery, showing it can be mounted at 0°.

UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	-