

BT14B-4

BS CODE: **300644**

VOLTAGE **12V**

CCA **210A**

CAPACITY 20HR **12.6Ah**

CAPACITY 10HR **12.0Ah**



DIMENSIONS

| | | |
|---------------------|------------|----------------|
| LENGTH | 150 ±2mm | 5.91 ±0.08inch |
| WIDTH | 70 ±2mm | 2.76 ±0.08inch |
| TOTAL HEIGHT | 145 ±2mm | 5.71 ±0.08inch |
| WEIGHT | 4.1 kg ±5% | 9.04 lbs ±5% |

TERMINAL (mm)

| | | |
|-----------------|------|-----|
| POLARITY | | |
| | | |
| FRONT | SIDE | TOP |

SLA FEATURES

- FACTORY ACTIVATED**
AGM (Absorbent Glass Mat) technology.
- READY TO USE**
Just plug & play.
- NO MAINTENANCE**
VRLA (Valve Regulated Lead Acid) design.
- SPILL-PROOF DESIGN**
Factory sealed & electrolyte held in a glass fiber mat.
- NO ACID HANDLING**
Very safe.
- HIGH STARTING POWER & EXTENDED CYCLE LIFE**

MOUNTING ANGLE

UPGRADE FOR

| SLA MAX | SLA | MF | DRY |
|---------|-----|----------|-----|
| - | - | BT14B-BS | - |