

## BTX20HL

BS CODE: **300689**

VOLTAGE **12V**

CCA **310A**

CAPACITY 20HR **18.9Ah**

CAPACITY 10HR **18.0Ah**



DIMENSIONS		
<b>LENGTH</b>	175 ±2mm	6.89 ±0.08inch
<b>WIDTH</b>	87 ±2mm	3.43 ±0.08inch
<b>TOTAL HEIGHT</b>	155 ±2mm	6.1 ±0.08inch
<b>WEIGHT</b>	5.91 kg ±5%	13.03 lbs ±5%

TERMINAL (mm)	
<b>POLARITY</b>	
FRONT	SIDE
	TOP

SLA FEATURES	
	<b>FACTORY ACTIVATED</b> AGM (Absorbent Glass Mat) technology.
	<b>READY TO USE</b> Just plug & play.
	<b>NO MAINTENANCE</b> VRLA (Valve Regulated Lead Acid) design.
	<b>SPILL-PROOF DESIGN</b> Factory sealed & electrolyte held in a glass fiber mat.
	<b>NO ACID HANDLING</b> Very safe.
	<b>HIGH STARTING POWER &amp; EXTENDED CYCLE LIFE</b>

MOUNTING ANGLE	

UPGRADE FOR			
SLA MAX	SLA	MF	DRY
-	-	BTX20L-BS BTX20HL-BS	BB18L-A