

BTX24HL-BS

BS CODE: **300630**

VOLTAGE **12V**

CCA **350A**

CAPACITY 20HR **22.1Ah**

CAPACITY 10HR **21.0Ah**



DIMENSIONS

LENGTH	205 ±2mm	8.07 ±0.08inch
WIDTH	87 ±2mm	3.43 ±0.08inch
TOTAL HEIGHT	162 ±2mm	6.38 ±0.08inch
WEIGHT	5.67 kg ±5%	12.5 lbs ±5%

TERMINAL (mm)

POLARITY		
FRONT		TOP
SIDE		

MF FEATURES

- TO BE ACTIVATED**
AGM (Absorbent Glass Mat) technology.
- ACID PACK INCLUDED**
For initial filling.
- NO MAINTENANCE***
VRLA (Valve Regulated Lead Acid) design.
- TIGHTLY SEALED AFTER FILLING**
Electrolyte is held in a glass fiber mat.
- SUPERIOR POWER & EXTENDED CYCLE LIFE**
- LONG SHELF LIFE**
No need to be recharged while stocked (if not activated).

*once activated

MOUNTING ANGLE

UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	B50-N18L-A/A2/A3/12N18-3A