

BTX4L-BS+ / BTZ5S-BS

BS CODE: 300617

VOLTAGE **12V**

CCA **50A**

CAPACITY 20HR **4.2Ah**

CAPACITY 10HR **4.0Ah**



DIMENSIONS		
LENGTH	113 ±2mm	4.45 ±0.08inch
WIDTH	70 ±2mm	2.76 ±0.08inch
TOTAL HEIGHT	85 ±2mm	3.35 ±0.08inch
WEIGHT	1.06 kg ±5%	2.34 lbs ±5%

TERMINAL (mm)	
POLARITY	⊖ / ⊕
FRONT	
SIDE	
TOP	

MF FEATURES	
	TO BE ACTIVATED AGM (Absorbent Glass Mat) technology.
	ACID PACK INCLUDED For initial filling.
	NO MAINTENANCE* VRLA (Valve Regulated Lead Acid) design.
	TIGHTLY SEALED AFTER FILLING Electrolyte is held in a glass fiber mat.
	SUPERIOR POWER & EXTENDED CYCLE LIFE
	LONG SHELF LIFE No need to be recharged while stocked (if not activated).

*once activated

MOUNTING ANGLE	

UPGRADE FOR			
SLA MAX	SLA	MF	DRY
-	-	-	-