

# 12N5.5-3B

BS CODE: 310529

VOLTAGE **12V**

CCA **55A**

CAPACITY 20HR **5.8Ah**

CAPACITY 10HR **5.5Ah**



### DIMENSIONS

|                     |            |                |
|---------------------|------------|----------------|
| <b>LENGTH</b>       | 135 ±2mm   | 5.31 ±0.08inch |
| <b>WIDTH</b>        | 60 ±2mm    | 2.36 ±0.08inch |
| <b>TOTAL HEIGHT</b> | 130 ±2mm   | 5.12 ±0.08inch |
| <b>WEIGHT</b>       | 1.6 kg ±5% | 3.53 lbs ±5%   |

### TERMINAL (mm)

|                 |      |     |
|-----------------|------|-----|
| <b>POLARITY</b> |      |     |
|                 |      |     |
| FRONT           | SIDE | TOP |

### DRY FEATURES

- TO BE ACTIVATED**  
DRY-charged technology.
- ACID PACK INCLUDED**  
For initial filling.
- PERIODIC MAINTENANCE**  
Refilled with water if necessary.
- HANDLE WITH CARE TO PREVENT ACID SPILLAGE**
- LONG SHELF LIFE**  
No need to be recharged while stocked (if not activated).
- INTERNAL GAS EMISSION THROUGH VENTING HOLE**
- WIDE VARIETY OF 6V & 12V MODELS**

### MOUNTING ANGLE

### UPGRADE FOR

| SLA MAX | SLA | MF | DRY |
|---------|-----|----|-----|
| -       | -   | -  | -   |