

## BTX6.5L

BS CODE: 300904

VOLTAGE **12V**

CCA **85A**

CAPACITY 20HR **6.8Ah**

CAPACITY 10HR **6.5Ah**



### DIMENSIONS

<b>LENGTH</b>	139 ±2mm	5.47 ±0.08inch
<b>WIDTH</b>	66 ±2mm	2.6 ±0.08inch
<b>TOTAL HEIGHT</b>	102 ±2mm	4.02 ±0.08inch
<b>WEIGHT</b>	2.3 kg ±5%	5.07 lbs ±5%

### TERMINAL (mm)

<b>POLARITY</b>		
<b>FRONT</b>	<b>SIDE</b>	<b>TOP</b>

### SLA FEATURES

- FACTORY ACTIVATED**  
AGM (Absorbent Glass Mat) technology.
- READY TO USE**  
Just plug & play.
- NO MAINTENANCE**  
VRLA (Valve Regulated Lead Acid) design.
- SPILL-PROOF DESIGN**  
Factory sealed & electrolyte held in a glass fiber mat.
- NO ACID HANDLING**  
Very safe.
- HIGH STARTING POWER & EXTENDED CYCLE LIFE**

### MOUNTING ANGLE

### UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	-