

BTX7L-BS

BS CODE: **300620**

VOLTAGE **12V**

CCA **100A**

CAPACITY 20HR **6.3Ah**

CAPACITY 10HR **6.0Ah**



| DIMENSIONS | | |
|--------------|-------------|----------------|
| LENGTH | 113 ±2mm | 4.45 ±0.08inch |
| WIDTH | 70 ±2mm | 2.76 ±0.08inch |
| TOTAL HEIGHT | 130 ±2mm | 5.12 ±0.08inch |
| WEIGHT | 1.73 kg ±5% | 3.81 lbs ±5% |

| TERMINAL (mm) | |
|---------------|--|
| POLARITY | |
| | |
| | |

| MF FEATURES | |
|-------------|---|
| | TO BE ACTIVATED AGM (Absorbent Glass Mat) technology. |
| | ACID PACK INCLUDED For initial filling. |
| | NO MAINTENANCE* VRLA (Valve Regulated Lead Acid) design. |
| | TIGHTLY SEALED AFTER FILLING Electrolyte is held in a glass fiber mat. |
| | SUPERIOR POWER & EXTENDED CYCLE LIFE |
| | LONG SHELF LIFE No need to be recharged while stocked (if not activated). |

*once activated

| MOUNTING ANGLE | |
|----------------|--|
| | |

| UPGRADE FOR | | | |
|-------------|-----|----|-----|
| SLA MAX | SLA | MF | DRY |
| - | - | - | - |