

KATANA

HIGH TORQUE

100% SYNTHÉTIQUE



SPORT

API SP / JASO MA2



Available viscosity grades :

15W-50 / 15W-60 / 20W-50

KATANA HIGH TORQUE is a 100% synthetic 4-stroke motorcycle engine oil made of high-quality polyalphaolefins (PAOs), esters and additives. Designed to provide optimum protection at high temperatures and under very heavy loads, it is dedicated to high-capacity, high-torque engines. Ideal for cruisers, it promotes a smooth, high-performance driving experience.

PACKING UNITS :



TECHNICAL DATA :

TEST	MÉTHOD	TYPICAL VALUES			MEASURE UNITS
		15W-50	15W-60	20W-50	
Density at 20°C	ASTM D4052	0,871	0,876	0,871	g/cm ³
Viscosity at 40°C	ASTL D445 or ASTM D7279	125,5	152	130,1	Mm ² /s
Viscosity at 100°C	ASTL D445 or ASTM D7279	19	23,6	19,44	Mm ² /s
Viscosity Index (VIE)	ASTM D2270	172	187	171	-
Pour point	ASTM D97				°C
Flash point	ASTM D92	260	242	271	°C
TBN	ASTM D2896	7,08	7,08	7,08	mg KOH/g