

KATANA

OFF-ROAD

100% SYNTHETIC



API SP / JASO MA2



Available viscosity grades :

10W-40 / 10W-50 / 10W-60

KATANA OFF-ROAD is a 100% synthetic 4-stroke motorcycle engine oil made of high-quality polyalphaolefins (PAOs), esters and additives. Designed to offer very high off-road performance, it guarantees maximum protection under heavy load and excellent clutch control. Ideal for cross, enduro and enduro trail bikes, it promotes sharper revs and smooth, fast gear changes.

PACKING UNITS :



TECHNICAL DATA :

| TEST | METHOD | TYPICAL VALUES | | | MEASURE UNITS |
|-----------------------|-------------------------|----------------|--------|--------|--------------------|
| | | 10W-40 | 10W-50 | 10W-60 | |
| Density at 20°C | ASTM D4052 | 0,867 | 0,872 | 0,856 | g/cm ³ |
| Viscosity at 40°C | ASTL D445 or ASTM D7279 | 86 | 106 | 161,8 | Mm ² /s |
| Viscosity at 100°C | ASTL D445 or ASTM D7279 | 13,82 | 18,1 | 23,49 | Mm ² /s |
| Viscosity Index (VIE) | ASTM D2270 | 169 | 190 | 175 | - |
| Pour point | ASTM D97 | | | | °C |
| Flash point | ASTM D92 | 252 | 224 | 264 | °C |
| TBN | ASTM D2896 | 7,4 | 7,4 | 7,4 | mg KOH/g |